

Dishwashers

G 8066, G 8072

Tank wash system

High throughput performance making it ideal for busy kitchens in hotels and schools

Triple filter

Provides high hygiene level for extended tank operation

Clear visual operating display

Easy to operate controls with colour coding on G 8072

Wide range of baskets and tabling

Flexible and versatile solutions to suit most applications

Option of liquid detergent feed

Eliminates potential hazard associated with manual dosing



G 8066



G 8066 DOS



G 8072

Dishwasher

Design

Freestanding	x	x	x
Single basket chamber	x	x	x
Basket size: 500 mm x 500 mm, 500 mm x 530 mm, 530 mm x 530 mm	o	o	o

Controls

Touch control panel	x	x	x
---------------------	---	---	---

Programmes

Number of programmes	3	3	3
Duration (secs)	90 / 120 / 180	90 / 120 / 180	60 / 120 / 180
Self-cleaning programme	x	x	x

Tank

Capacity (litres)	17	17	45
Heating (kW)	0.75	0.75	1.8
Wash temperature °C (factory default)	65	65	65

Boiler

Capacity (litres)	6	6	12
Heating (kW)	9.25	9.25	9
Rinse temperature °C (factory default)	Wash temp. + 20°C	Wash temp. + 20°C	85

x Standard feature o Optional feature - Feature not available

Miele
PROFESSIONAL

Dishwasher

	G 8066	G 8066 DOS	G 8072
Dispenser systems			
Internal pump for rinse aid	x	x	x
Internal reservoir for rinse aid	-	x	-
Internal pump for detergent	-	x	o
Internal reservoir for detergent	-	x	-
Socket connection for external liquid dispensing pump	x	-	x
G 60 external liquid dispensing pump	o	-	o
Water softener			
Built-in, up to 25°dH	-	-	o
Built-in, up to 30°dH	o	o	-
Circulation pump			
Throughput [l/min]	400	400	800
Plumbing			
1 x cold/hot water 1/2" with 3/4" threaded union (max 65°C)	x	x	x
Built-in rinse booster pump	x	x	x
Inlet pressure 100 - 1000 kPa	x	x	-
Inlet pressure 80 - 600 kPa	-	-	x
Drain pump	x	x	x
Maximum head	1 m	1 m	0.65 m
Electrical connection			
1N AC 220-240 V 50 Hz with cable	6.4 kW / 1 x 32A	-	-
1N AC 220-240 V 50 Hz with cable (load interlocked)	-	-	7.7 kW / 1 x 32A
3N AC 400 V 50 Hz with cable (load unlocked)	-	10.5 kW / 3 x 16A	9.5 kW / 3 x 16A
3N AC 400 V 50 Hz with cable (load interlocked)	-	-	10.7 kW / 3 x 16A
Dimensions, weight			
Height without lid / including optional lid (mm)	820 / 850	820 / 850	-
Height hood lowered / hood raised (mm)	-	-	1470 / 1940
Width x depth (mm)	598 x 600	598 x 600	800 x 880
Net weight [kg]	70	71	118
External casing			
Stainless steel	x	x	x
DET 60/1 stainless steel lid	o	o	-
Sound levels (IEC 704-1 and 704-2-4)			
Noise level	60.2 dB	60.2 dB	75.1 dB

x Standard feature o Optional feature - Feature not available

Miele Professional preserves the right to change the machines and specification at anytime, without any prior notice. All information printed is only for information and never legally binding.



For all enquiries, please contact Miele Professional

Miele Company Limited, Fairacres,
Marcham Road, Abingdon, OX14 1TW
www.Miele-Professional.co.uk

E: miele-professional@miele.co.uk
T: 01235 233 523
F: 01235 405 636

Miele
PROFESSIONAL