

Roller length	mm	830
Roller diameter	mm	160 incl. padding
Type of heating		Electric
Packaging dimensions normal/sea freight	W mm D mm H mm	1110 / ... 445 / ... 1010 / ...
Gross weight	normal kg Sea freight kg	44
Machine dimensions overall	W mm D mm H mm	1050 380 960
Net weight	kg	38
Max. floor load in operation	N	372
Total rated load (EL)	kW	3,06 at 230 V and 400 V
Heater rating	kW	3,0 at 230 V and 400 V
Motor rating	Roller drive W Trough drive W Fan W	60 -
Fuse rating ³	3N AC 380-415V 50-60Hz A 3 AC 220-240V 50-60Hz A 220-240V 50-60Hz A	2 x 10 1 x 16
Connection EL ⁴	3N AC 380-415V 50-60Hz mm ² 3 AC 220-240V 50-60Hz mm ² 220-240V 50-60Hz mm ²	4 x 1,5 3 x 1,5
Connections	HD-steam Condensate Gas Exhaust air / exhaust gas	- - - -
Ironing performance ⁵	kg/h according to DIN 11902	up to 15
Roller	Rotational speed 1/min Circumference speed m/min Contact pressure; norm. N/cm ²	4,0 - 9,0 (adjustable in 5 steps) 2,0 - 4,5 0,35
Fan capacity (0 bar) max. permissible pressure loss	m ³ /h	
Material	Side columns Roller Trough	Aluminium, stove-finished Sheet metal zinc-plated Aluminium, hard anodized
Largest removable component		
Dissassembly / Assembly time	approx. h	

Heat dissipation to installation place: 11,4 MJ/h
Noise power level: dB (A) according to DIN 45635

Test marks:

Padding: Polyester needle-felt mat with Aramid-Needle felt cloth (2 % stainless steel fibres)

- 1) operating category: gL
- 2) Min. cross section according to VDE 0100 part 430 / group 2
- 3) relating to sheets (fibre quality according to TB 21)
up to 20% residual moisture - sheets put in directly one after the other without gaps
(air dry according to DIN 11901); max. temperature of the trough 180°C