

Load capacity (dry laundry)	6.5 kg		
Type of heating	Electric		
Packaging dimensions	W	mm	660 mm
Standard/Sea freight	D	mm	770 mm
	H	mm	940 mm
Gross weight	Normal	kg	64
	Sea freight	kg	-
Machine dimensions	W	mm	595
Overall dimensions	D	mm	700
	H	mm	850
Net weight			kg
			58
Max. floor load in operation			N
			680
Total rated load (EL)			kW
			6.44 kW
Heater rating			kW
			6.14 ¹
Motor rating	Drive	W	-
	+ fan	W	300
	Condensate pump	W	-
Fuse rating ²			
	3N AC 400 V 50 Hz		3 x 10
	3 AC 230V 50Hz	A	1 x 16
	1N AC 400 V 50 Hz	A	1 x 16
Supply lead EL ³			
	3N AC 400 V 50 Hz	mm ²	5 x 1.5
	3 AC 230V 50Hz	mm ²	3 x 1.5
	1N AC 400 V 50 Hz		3 x 1.5
Vented	DN 100		
Evaporation approx.	l/h		5.6
	<u>Residual moisture</u>		<u>Setting</u>
		55%	
		51	1 Extra dry
		42	2 Normal dry +
		41	3 Normal dry
		36	4 Hand iron 0
		33	5 Hand iron 00
		28	6 Machine iron
Duration / Load ⁶ according to EN 61121	mins.		
		4.7	1 Extra dry
		3.7	2 Normal dry +
		3.6	3 Normal dry
		3.0	4 Hand iron 0
		2.7	5 Hand iron 00
		2.2	6 Machine iron
Energy requirements / Load according to EN 61121	kWh		

Fan	Throughput (0 mbar) m ³ /h Max. permissible pressure loss m ³ /h Max. permissible pressure loss Pa	310 m ³ /h unconnected 100 m ³ /h at max. permissible pressure loss 250 Pa
-----	--	---

Drum	Diameter	mm	566
	Depth	mm	557
	Contents	l	130
	Drum speed	rpm	54
	Circ. speed	m/s	1.6
	∅ Door opening	mm	470
Material	Plinth		
	Drum		Stainless steel 1.4301
	Air duct		Plastic
	Casing		Enamelled or stainless steel (optional)
Largest removable component			-

Heat dissipation: 0.76 MJ/h

Sound power level: 65 dB re 1pW according to IEC 60704-3

Test marks: IP X4, VDE, VDE-EMC, CE

- 1) convertible to 2.99 kW on 1 AC 230V 50Hz supply
- 2) Trip characteristics B (EN 60898)
- 3) Min. cross-section according to VDE 0100 Part 430 / Group 2
- 4)
- 5)
- 6) incl. 10 mins. 'Cool air'
- 7)
- 8)