

Load capacity (dry laundry)			8.0 kg / load ratio 1 : 22.5						
Type of heating			Electric		Gas ¹				
Packaging dimensions normal/seafreight	B	mm	760 / -		760 / -				
	T	mm	820 / -		820 / -				
	H	mm	1215 / -		1215 / -				
Net weight	normal	kg	88		89				
	seafreight	kg	-						
Machine dimensions Overall (casing)	B	mm	700		700				
	T	mm	763		763				
	H	mm	1020		1020				
Net weight		kg	77		78				
Max. floor load in operation		N	1000		1000				
Total rated load (EL)					0.40 – 0.46				
	3N AC 400V 50Hz	kW	8.5						
	3 AC 230V 50Hz	kW	8.5						
	AC 230V 50Hz	kW	5.8						
	3 AC 440V 60Hz	kW	8.5						
Heater rating					Nat. Gas G20, with 15°C; 1013 mbar Heating capacity 8 / 6 kW (H _i)				
	3N AC 400V 50Hz	kW	7.94						
	3 AC 220-240V 50Hz	kW	7.94						
	AC 220-240V 50Hz	kW	5.22						
	3 AC 440V 60Hz	kW	7.94						
Motor rating	Drive	W	220		220				
	Fan	W	180		180				
Fuse rating ²					1 x 10				
	3N AC 400V 50Hz	A	3 x 16						
	3 AC 220-240V 50Hz	A	3 x 25						
	AC 220-240V 50Hz	A	1 x 25						
	3 AC 440V 60Hz	A	3 x 16						
Connection EL ³					3 x 1.5				
	3N AC 400V 50Hz	mm ²	5 x 1.5						
	3 AC 220-240V 50Hz	mm ²	4 x 2.5						
	AC 220-240V 50Hz	mm ²	3 x 2.5						
	3 AC 440V 60Hz	mm ²	4 x 1.5						
Air intake/venting			DN 100		DN 100				
Max. evaporation rate ⁹		ca. l/h	8.1		8.1				
Residual moisture ^{4/5}			50	55	50	55			
Drying time ^{4/5/6/11/12}	Min	Pr	Rf						
		1	0%	37	40	35	39		
		2	25%	16	18	16	18		
					Electric	Gas	Electric	Gas	
Energy consumption ^{4/5/6/11/12}		kWh	1	3.8	4.2	0.22	3.9	0.25	4.4
			2	2.0	2.2	0.13	1.3	0.15	1.6

Type of heating		Electric	Gas
Drum	Diameter	mm	650
	Depth	mm	540
	Contents	l	180
	Spin speed	1/min	50.1
	Circumference speed	m/s	1.71
	∅ Door opening	mm	440
Fan	Max. circulation capacity	m³/h	320 unconnected
	Exhaust air	m³/h	180 at max. permissible pressure loss
	Max. permissible pressure loss	mbar	4.2
			310 unconnected 215 at max. permissible pressure loss 4
Plinth Material	Drum	galvanised	
	Air duct	Stainless steel 1.4301 / 1.4016	
	Casing	Plastic	
		Stove-finished white	
Largest removable component		Drum: ∅ 650 mm x 540 mm	

Heat dissipation to ambient room: 450 W ¹³⁾

Noise pressure level at the workstation: <70dB(A) according EN ISO 11203,11204

Noise power level: 64,9 dB according DIN EN 60704-2 Part 1,6

Test marks: CE, EMV-VDE, VDE

- 1) Natural gas G20, by 15°C; 1013 mbar according DIN EN 12752 Part 1
- 2) Operating category: gL
- 3) Min. cross-section according to VDE 0100 Part 430 / Group 2
- 4) Type of laundry: Programme 1 Turkish towels
2 Cottons according to DIN EN 61121
- 5) Residual moisture calculated according to DIN EN 61121
- 6) Including "Cold air"
- 7)
- 8)
- 9) Evaporation based on RM 70% to 0%
- 10) Values may vary according to type of laundry
- 11) Values adjusted to 55% residual moisture and 23°C ambient room temperature
- 12) Values refer to entire programme duration (incl. cool-down)
- 13) Depending on programme chosen and ambient room temperature

Cottons	Programme 1	- "Cottons Dry"	0% residual moisture
	Programme 2	- "Cottons Dry+"	25% residual moisture