

Dishwashers

G 7855, G 7856, G 7859

Programmes to suit a wide range of applications

Fresh water wash system

85°C rinse temperature on G 7859

Wide range of baskets and accessories

Option of liquid detergent feed




Ideal for guest houses, gastro pubs, coffee shops, tea rooms and day nurseries

Provides high hygiene level

Meets with Department of Health guidelines for dishwashing in hospital ward kitchens. Ideal for installation in care and nursing homes

Flexible and versatile solutions to suit most applications

Eliminates potential hazard associated with manual dosing

Dishwasher			
	G 7855	G 7856	G 7859
Design			
Freestanding	x	x	x
Top & bottom basket inc. 2 x cutlery inserts plus 2 x plate racks	x	x	x
Built-in steam condenser	-	-	x
Electro-thermal door lock	-	-	x
Controls			
MULTITRONIC NOVO VARIO	x	x	x
Number of programmes	7	8	4
Programme times (cold water @ 15°C)*, main wash °C / rinse °C		See footnote	See footnote
Super Short 55 / 55	-	11 mins ¹	-
Short 55 / 60	22 mins	16 mins ¹	-
Short 65 / 85	-	-	22 mins ¹
Universal 55 / 60	27 mins	22 mins ¹	-
Universal 65 / 85	-	-	28 mins ¹
Universal Plus 60 / 60	29 mins	23 mins ¹	-
Intensive 65 / 60	33 mins	28 mins ¹	-
Intensive 65 / 85	-	-	31 mins ¹
Glassware 50 / 50	18 mins	16 mins ¹	-
Beer glasses 50 /	15 mins	13 mins ¹	-
Cold rinse	4 mins	4 mins	4 mins
Programme times (hot water @ 65°C)*, main wash °C / rinse °C		See footnote	See footnote
Super Short 55 / 55	-	7 mins ¹	-
Short 55 / 60	15 mins	11 mins ¹	-
Short 65 / 85	-	-	18 mins ¹
Universal 55 / 60	22 mins	17 mins ¹	-
Universal 65 / 85	-	-	24 mins ¹
Universal Plus 60 / 60	24 mins	18 mins ¹	-

¹ Data is for 400V version *Excludes drying cycle x Standard feature o Optional feature - Feature not available

Miele
PROFESSIONAL

Dishwasher

	G 7855	G 7856	G 7859
Controls continued		See footnote	See footnote
Intensive 65 / 60	26 mins	21 mins ¹	-
Intensive 65 / 85	-	-	27 mins ¹
Glassware 50 / 50	15 mins	12 mins ¹	-
Beer glasses 50 /	15 mins	12 mins ¹	-
Cold rinse	4 mins	4 mins	4 mins
Dispenser systems			
Powder dispenser in door	x	x	x
Rinse aid dispenser in door	x	x	x
Socket connection for external liquid dispensing pump	x	x	x
G 60 external liquid dispensing pump	o	o	o
Water softener			
Built-in, up to 60°dH	x	x	x
Circulation pump			
Throughput [l/min]	400	400	400
Plumbing			
1 x Cold/hot water 1/2" with 3/4" threaded union	x	-	-
1 x cold and 1 x hot water 1/2" with 3/4" threaded union	-	x	x
Drain pump	x	x	x
Maximum head	1 metre	1 metre	1 metre
Electrical connection			
1N AC 220-240 V 50 Hz with cable	6.4 kW / 1 x 32A	6.4 kW / 1 x 32A	6.4 kW / 1 x 32A
3N AC 400 V 50 Hz with cable	-	9 kW / 3 x 16A	9 kW / 3 x 16A
Dimensions, weight			
External dimensions H/W/D [mm]	850 x 600 x 600	850 x 600 x 600	850 x 600 x 600
Net weight [kg]	70	70	76
External finish			
Front and sides white, laminated lid, anthracite fascia	x	x (230V)	x (230V)
Front, sides and lid stainless steel, anthracite fascia	-	o	o
Door/panel dimensions			
M-DER décor frame kit to accept décor panel	o	o	o
Décor panel thickness 1.2 mm max. H x W: 570.5 mm x 587 mm	Non-Miele supply	Non-Miele supply	Non-Miele supply
Sound levels (IEC 704-1 and 704-2-4)			
Noise level	52 dB	52 dB	52 dB

Wash programme times: durations shown are approximate for guidance. Factors such as type and nature of wash load and their effect on the thermo-stop can very much influence programme duration.

¹ Data is for 400V version *Excludes drying cycle x Standard feature o Optional feature - Feature not available

Miele Professional preserves the right to change the machines and specification at anytime, without any prior notice. All information printed is only for information and never legally binding.



For all enquiries, please contact Miele Professional

Miele Company Limited, Fairacres,
Marcham Road, Abingdon, OX14 1TW
www.Miele-Professional.co.uk

E: miele-professional@miele.co.uk
T: 01235 233 523
F: 01235 405 636

Miele
PROFESSIONAL