

Load capacity (dry laundry)	6.5 kg		
Type of heating	Electric		
Packaging dimensions	W	mm	660 mm
Standard/Sea freight	D	mm	770 mm
	H	mm	940 mm
Gross weight	Normal	kg	66
	Sea freight	kg	-
Machine dimensions	W	mm	595
Overall dimensions	D	mm	700
	H	mm	850
Net weight		kg	60
Max. floor load in operation		N	680
Total rated load (EL)		kW	3.75 kW
Heater rating		kW	3.45 ¹
Motor rating	Drive	W	
	+ fan	W	210
	Condensate pump	W	20
Fuse rating ^{1,2}			
	2N AC 400 V 50 Hz		3 x 10
	3 AC 230V 50Hz	A	3 x 16
	1N AC 400 V 50 Hz		1 x 16
	1N AC 400 V 50 Hz		1 x 10
Supply lead EL ³			
	2N AC 400 V 50 Hz	mm ²	4 x 1.5
	3 AC 230V 50Hz	mm ²	4 x 1.5
	1N AC 400 V 50 Hz		3 x 1.5
	1N AC 400 V 50 Hz		3 x 1.5
Evaporation approx.		l/h	2.6
	<u>Residual moisture</u>		
		55%	<u>Setting</u>
Duration / Load ⁶		102	1 Extra dry
according to EN 61121	mins.	93	2 Normal dry +
		89	3 Normal dry
		73	4 Hand iron 0
		67	5 Hand iron 00
		56	6 Machine iron
Energy requirements / Load		4.3	1 Extra dry
according to EN 61121	kWh	3.8	2 Normal dry +
		3.6	3 Normal dry
		3.2	4 Hand iron 0
		2.9	5 Hand iron 00
		2.3	6 Machine iron

Drum	Diameter	mm	566
	Depth	mm	557
	Contents	l	130
	Drum speed	rpm	54
	Circ. speed	m/s	1.6
	∅ Door opening	mm	470
Material	Plinth	Stainless steel 1.4301	
	Drum	Plastic	
	Air duct	Enamelled or stainless steel (optional)	
	Casing		
Largest removable component			-

Heat dissipation: 9.0 MJ/h

Sound power level: 68 dB re 1pW according to IEC 60704-3

Test marks: IP X4, VDE, VDE-EMC, CE

- 1) convertible to 1.94 kW on 1 AC 230V 50Hz, 10 A supply
- 2) Trip characteristics B (EN 60898)
- 3) Min. cross-section according to VDE 0100 Part 430 / Group 2
- 4)
- 5)
- 6) incl. 10 mins. 'Cool air'
- 7)
- 8)