

Load capacity (dry laundry)			5.5 kg				
Type of heating			Electric				
Packaging dimensions	W	mm	660 / ...				
Standard/Sea freight	D	mm	770 / ...				
	H	mm	940 / ...				
Gross weight	Normal	kg	116				
	Sea freight	kg					
Machine dimensions	W	mm	595				
Overall dimensions	D	mm	700				
	H	mm	850				
Net weight		kg	104				
Max. floor load in operation		N	2820				
Frequency		Hz	24.0				
Total rated load (EL)		kW	5.5				
Heater rating		kW	5.3 ¹				
Rating	Drive	W	Wash 200; Pre-spin - ; Spin 400				
Motor	Drain pump ²	W	40 (max. head height 100 cm)				
	Circulation pump		-				
Fuse rating ³	2N AC 400 V 50 Hz	A	2 x 16				
	AC 230V 50Hz	A	1 x 16				
Supply lead EL ⁴	2N AC 400 V 50 Hz	mm ²	4 x 1.5				
	AC 230V 50Hz	mm ²	3 x 1.5				
Connection	Water	Cold Cold-Raw Hot≤70°C	1 x pressure hose DN 10 with 3/4" threaded union, 1.5 m				
	Drainage	Drain throughput	1 x pressure hose DN 10 with 3/4" threaded union, 1.5 m				
			DN 70; with DN 22 drain pump approx. xxx l/min				
Wash drum	Diameter	mm	480	rpm Circumferential speed m/s g-factor	Wash	Pre-spin	Spin
	Depth	mm	274		30/40/50		1400
	Contents	l	55		0,75/1,0/1,27		35.2 m/s
	∅ Door opening	mm	300		0,24/0,43/0,67		526
Residual moisture according to DIN 60456 ⁷			approx. 50%				
Necessary water flow pressure			min. 1 bar ; max. 10 bar				
Largest removable component Assembly/Disassembly approx.							
Material	Plinth		Stainless steel 1.4520				
	Drum		Stainless steel 1.4510/20 , 1.4016				
	Suds container		Enamelled / Stainless steel				
	Casing						

Type of heating			Electric with drain valve		Electric with drain pump		
Rate of temperature increase (low water level) K/min			3		3		
approx. consumption/cycle ⁷ in accordance with DIN EN 60456			CW	HW 70°C	CW	HW 70°C	
95°C prog.	Energy consumption		1.8	0.8	1.8	0.8	
	Heating	kWh					
60°C	Water	EL	49	35	49	35	
		Cold					l
		Cold-Raw					1
	Hot	1					
Duration ⁸ Normal/Intensive mins.		69 / 99	59 / 79	69 / 99	59 / 79		
60°C prog.	Energy consumption		1.0	0.3	1.0	0.3	
	Heating	kWh					
	Water	EL	49	36	49	36	
		kalt					l
Cold-Raw		1					
Hot	1						
Duration ⁸ Normal/Intensive mins.		59 / 94	49 / 69	59 / 94	49 / 69		
40°C prog.	Energy consumption		0.45	0.15	0.45	0.15	
	Heating	kWh					
	Water	EL	53	47	53	47	
		Cold					l
Cold-Raw		1					
Hot	1						
Duration ⁸ Normal/Intensive mins.		45 / 60	40 / 55	45 / 60	40 / 55		
+ CD							

Kinetic energy: 1711 Nm
Heat dissipation: 1.0 MJ/h
Sound power level¹⁰: Wash 52 dB; Spin 71 dB re 1pW

Test marks: VDE / VDE-EMC

- 1) convertible to 2.65 kW on 1 AC 230V 50Hz supply (heater rating)
- 2) On request
- 3) Operation category: gL
- 4) Min. cross-section according to VDE 0100 Part 430 / Group 2
- 5)
- 6)
- 7) Standard load A
- 8) with water flow pressure of 3 bar
- 9)
- 10) according to IEC 704-1 and 704-2-4

Date: 13.03.2006

Author: Scheidler

All rights reserved!