

Rotary Ironers

HM 16-80, HM 16-83

- Powerplus** Aluminium heater plates provide outstanding heat distribution and up to four times faster heat-up time than steel heater plates.
- Careplus** Adjustable temperature control and roller speed provide optimal textile care.
- Flexplus** The steam facility of the HM 16-80 together with an open ended roller provides a high degree of flexibility.
- Volumeplus** High throughput of up to 15kg per hour depending on model.
- Ecoplus** Durable needle-felt roller cover for long service life.
- Comfortplus** Ergonomic controls with ironing easily carried out by one operator in a seated position.



Rotary Ironer

HM 16-80

HM 16-83

Design

Rigid frame, return feed operation	-	x
Folding frame with steam facility	x	-

Roller specification

Length [mm]	830	830
Diameter [mm]	160	160
Rotational speed [l/min]	4 - 9	4 - 9
Circumference speed [m/min]	2 - 4.5	2 - 4.5
Contact pressure [N/cm ²]	0.35	0.35

Water tank specification

Tank capacity [ml]	approx 840	-
Steam time [min]	approx 6	-

Ironing performance

Throughput according to DIN 11902 [kg/h]*	Up to 13	Up to 15
---	----------	----------

*Up to 20% residual moisture, sheets fed without gaps; maximum trough temperature 180°C

x Standard feature - Feature not available

Rotary Ironer		
	HM 16-80	HM 16-83
Heating		
Electric (EL), Gas (G), Steam (D)union	EL	EL
Electrical connection		
1N AC 220-240 V 50-60 Hz with cable and plug	2.7 - 3.2 kW / 1 x 13 A	2.6 - 3.1 kW / 1 x 13 A
Dimensions, weight		
Height [mm]	959	959
Width [mm]	985	1050
Depth [mm]	380	380
Height when folded [mm]	1052	-
Width when folded [mm]	500	-
Depth when folded [mm]	385	-
Net weight [kg]	39	38
Floor load		
Maximum floor load in operation	382 N	372 N
Frequency	-	-

*Up to 20% residual moisture, sheets fed without gaps; maximum trough temperature 180°C
x Standard feature - Feature not available

Miele Professional preserves the right to change the machines and specification at anytime, without any prior notice.
All information printed is only for information and never legally binding.

For all enquiries, please contact Miele Professional

Miele Company Limited, Fairacres,
Marcham Road, Abingdon, OX14 1TW
www.Miele-Professional.co.uk

E: miele-professional@miele.co.uk
T: 01235 233 523
F: 01235 405 636

Miele
PROFESSIONAL