

Miele PROFESSIONAL			Rotary ironer HM 5316	06/95
Roller length	cm		165	
Padded roller diameter	cm		25	
Type of heating			Electric	
Packaging dimensions	W	cm	233 / 235	
Normal/sea	D	cm	80 / 90	
	H	cm	137 / 133	
Gross weight	Normal	appr. kg	301	
Machine dimensions	W	cm	216	
	D	cm	59	
	H	cm	104	
Net weight		appr. kg	216	
Max. floor load in operation		N	2119	
Total rated load (EL)		kW	11.9	
Heater rating		kW	11.0	
Motor rating	Roller drive	W	400	
	Heater plate	W	400	
	Fan	W	100	
Fuse rating				
	3N AC 380-400V 50-60Hz	A	3 x 20	
	3 AC 220-230V 50-60Hz	A	3 x 35	
	220-230V 50-60Hz	A		
Supply lead cross-section EL				
	3N AC 380-400V 50-60Hz	mm ²	5 x 2.5	
	3 AC 220-230V 50-60Hz	mm ²	4 x 6	
	220-230V 50-60Hz	mm ²		
Connections	HP steam		-	
	Condensate		-	
	Gas		-	
	Waste air/waste gas		70 mm	
Max. laundry throughput ¹		kg/h	47	
Roller	Speed	rpm	1.5 - 5.0	
	Linear speed	m/min	1.2 - 3.9	
	Contact pressure	N/cm ²	0.7	
Fan	Max. capacity	m ³ /h	115 (unrestricted)	
	Max. pressure loss	mbar	1	
Material	Side columns		Galvanised, stove-finished sheet steel	
	Roller		Galvanised, stove-finished sheet steel	
	Heater plate		Anodised aluminium	
Largest removable part			Heater plate: 1638 x 120 x 280 mm (W x D x H)	
Removal / installation time		appr. h	6.0 / 6.0	

Heat dissipation rate: .. MJ/h
Noise emission: 65.3 dB (A)

Test certificates: TÜV - GS; Interference suppression;

Padding: Steel wool with Aramid needle felt cloth

1) Referring to sheets (25% residual moisture, fed through in direct succession) dried to 0% residual moisture (bone dry) at max. heater plate temperature of 180°C