




Little Giant Washer-Extractors

PW 5064, PW 6055 Vario, PW 6065 Vario

- Powerplus** A performance that offers more with powerful heater elements for fast heat-up and short cycles. Large drum volume for high laundry loads and intelligent solutions for reliable results - Professional, commercial technology.
- Careplus** The patented honeycomb drum ensures laundry is cared for. The profiled pattern on the drum creates a protective film of water on which clothing gently slides.
- Flexplus** Profitronic L Vario controls - Electronic controls with multi-function selector and user navigation screen. Programme delay and time left display to enable the user to manage their time efficiently. Wide range of standard programmes as well as a number of special programmes such as table linen, pillows and outerwear & reproofing.
- Ecoplus** A sustainable, cost effective performance, achieving optimum results using as little water, energy and detergent as necessary. Robust design using recyclable materials for maximum sustainability.
- Comfortplus** A simple, user-friendly solution when selecting programmes by using rotary switch and pushbuttons. With a large drum opening for simple loading and unloading.

Washer-extractor			
	PW 5064	PW 6055 Vario	PW 6065 Vario
Design			
Suitable for stacking	x	x	x
Door opening Frontloader: [Ø mm]	300	300	300
Capacity			
Max. load [kg]	6.5	5.5	6.5
Honeycomb drum volume [litres]	59	54	59
Moisture control	See footnote		
Spin speed [max. rpm]	1400	1400	1400
g factor	526	526	526
Residual moisture %	22 ¹	49	49
Controls			
NOVOTRONIC L	x	-	-
PROFITRONIC L Vario	-	x	x

¹ Ref. floor mops x Standard feature o Optional feature - Feature not available

Miele
PROFESSIONAL

Washer-extractor

	PW 5064	PW 6055 Vario	PW 6065 Vario
Dispenser systems			
3 compartment dispenser in machine front	x	x	x
Connection options			
External liquid dispensing interface	x	-	x
Payment system	o	o	o
Plumbing			
1 x Cold water 1/2" with 3/4" threaded union	x	x	x
1 x Hot water, 1/2" with 3/4" threaded union	x	x	x
Min. flow pressure 100 kPa (1 bar)	x	x	x
Max. flow pressure 1000 kPa (10 bar)	x	x	x
Drain pump DN 22	-	x	x
Dump valve DN 70	x	-	x
Heating			
Electric (EL), Gas (G), Steam (D)	EL	EL	EL
Electrical connection * (electric heating)			
1N AC 220-240 V 50 Hz with cable and plug	2.85 kW / 1 x 13 A	2.85 kW / 1 x 13 A	-
1N AC 220-240 V 50 Hz with cable	5.05-6.0 kW / 1 x 30 A	5.05-6.0 kW / 1 x 30 A	5.05-6.0 kW / 1 x 30 A
2N AC 400 V 50 Hz with cable	-	5.5 kW / 2 x 16 A	5.5 kW / 2 x 16 A
3 AC 440V 60 Hz	-	-	5.5 kW / 3 x 16 A
Dimensions, weight			
External dimensions H/W/D [mm]	850/595/725	850/595/725	850/595/725
Net weight [kg]	109	107	109
External finish			
Front, sides, fascia and lid white	x	-	-
Front and sides white, fascia and lid stainless steel	-	x	x
Front, fascia panel, sides and lid stainless steel	-	-	o
Sound levels (IEC 704-1 and 704-2-4)			
Wash	52 dB	52 dB	52 dB
Spin	71 dB re 1pW	71 dB re 1pW	71 dB re 1pW
Floor load			
Maximum floor load in operation	2820 N	2820 N	2820 N
Frequency	24 Hz	24 Hz	24 Hz

- 1 Ref. floor mops x Standard feature
o Optional feature - Feature not available

Miele Professional preserves the right to change the machines and specification at anytime, without any prior notice. All information printed is only for information and never legally binding.



COMPLIANT WITH MACHINERY GUIDELINE 2006/42/EC



WRAS APPROVED PRODUCT

For all enquiries, please contact Miele Professional

Miele Company Limited, Fairacres,
Marcham Road, Abingdon, OX14 1TW
www.Miele-Professional.co.uk

E: miele-professional@miele.co.uk
T: 01235 233 523
F: 01235 405 636

Miele
PROFESSIONAL