

Load capacity (dry laundry)				10 kg / 13 kg / Load ratio 1 : 25 / 1 : 20					
Type of heating				Electric		Gas ¹			
Packaging dimensions	W	mm	1036 / 1125		1036 / 1125				
	Normal/Sea freight	D	mm	966 / 1055		966 / 1055			
		H	mm	1598 / 1776		1598 / 1776			
Gross weight	Normal	kg	170		171				
	Sea freight	kg							
Machine dimensions	W	mm	906		906				
	Overall (casing)	D	mm	852 (752)		852 (752)			
		H	mm	1400		1400			
Net weight		kg	148		149				
Max. floor load in operation ³				1636		1651			
Total rated load (EL)		kW	14,3		0,8				
Heater rating		kW	13,5 ⁴		15				
Motor rating	Drive	W	300		300				
	Fan	W	400		400				
	Air baffle	W	20		20				
Fuse rating ⁵					1 x 10 (1N AC)				
3N AC 380-415V 50Hz		A	3 x 25						
(1N AC)3 AC 220-240V 50Hz		A	3 x 50						
3 AC 440V 60Hz		A	3 x 25						
Connection EL ⁶					3 x 1,5 (1N AC)				
3N AC 380-415V 50Hz		mm ²	5 x 4						
(1N AC)3 AC 220-240V 50Hz		mm ²	4 x 10						
3 AC 440V 60Hz		mm ²	4 x 4						
Connections									
HP steam			-		-				
Condensate			-		-				
Gas			-		1/2"				
Air intake / Venting		mm	DN 150		DN 150				
max. evaporation rate ⁹		l/h	13,6		15,0				
Evaporation based on 70% to 0%									
Initial residual moisture ^{7/8}		%	50		50				
Load capacity		kg	10	13	10	13			
Specific energy consumption in kWh/kg of water			0,95	0,98	1,08	1,04			
Drying time ^{7/8/10/11/12}	Min	Pr.	Rm						
		2	0%	22	31	23	28		
		4	25%	13	16	11	13		
Energy consumption ^{7/8/10/11/12}					Gas	EI	Gas	EI	
	kWh	2	0%	4,8	6,1	5,2	0,2	6,1	0,2
		4	25%	2,8	3,3	2,6	0,1	3,1	0,1

Type of heating		Electric	Gas						
Drum	Diameter	mm	850						
	Depth	mm	448						
	Contents	l	250						
	Spin speed	rpm	41						
	Circumference speed	m/s	1,82						
	Ø Door opening	mm	520						
Fan	Circulation capacity (0 mbar) at max. permissible dynamic pressure of 3 mbar	m ³ /h	<table border="1"> <tr> <td>440 / 560*</td> <td>510 / 560*</td> </tr> <tr> <td>310 / 510*</td> <td>430 / 510*</td> </tr> <tr> <td>*Profitronic M</td> <td>*Profitronic M</td> </tr> </table>	440 / 560*	510 / 560*	310 / 510*	430 / 510*	*Profitronic M	*Profitronic M
440 / 560*	510 / 560*								
310 / 510*	430 / 510*								
*Profitronic M	*Profitronic M								
Material	Plinth	Galvanised sheet steel							
	Drum	Chrome steel 1.4016							
	Air duct	Galvanised sheet steel							
	Casing	Galvanised sheet steel, powder-coated, Octoblue							
	Option: Front panel	Chrome nickel steel 1.4301							
Largest removable component		Dryer drum: Ø 858 mm / Depth 504 mm							
Disassembly/Assembly time approx. h		2,5 / 3,0							

Heat dissipation to ambient room: 509 W

Acoustic pressure level: L_{PA} 55 dB (A)

Acoustic power level: L_{WA} 68,6 dB (A) according to ISO 9614 Part 2

Test marks:

- 1) Natural gas / Liquid gas
- 2) Values apply for 8 bar steam pressure
- 3) Laundry weight with 50% residual moisture
- 4) Convertible to 9,0 kW or ... kW
- 5) Operating category: gL
- 6) Min. cross-section according to VDE 0100 Part 430 / Group 2
- 7) Type of laundry: Programme 1, 2 Turkish towels (50% RM)
3, 4, 5 Cottons – Standard load (A) (50% RM)
- 8) Residual moisture calculated according to DIN 11901 and DIN 11902
- 9) Evaporation based on RM 70% to 0% without cool-down phase
- 10) Values may vary according to type of laundry
- 11) Values adjusted to 50% residual moisture and 23°C ambient room temperature
- 12) Values refer to entire programme duration (incl. cool down to 50°C)

Cottons

Programme 2	- Cottons dry	0% Residual moisture
Programme 4	- Cottons moist I	25% Residual moisture