

Load capacity (dry laundry)			32 / 40 kg / Load ratio 1 : 25 / 1 : 20									
Type of heating			Electric		Gas ¹		HP Steam ²					
Packaging dimensions Normal/Sea freight	W	mm	1336 / 1425		1336 / 1425		1336 / 1425					
	D	mm	1530 / 1619		1530 / 1619		1530 / 1619					
	H	mm	1848 / 2026		1848 / 2026		1848 / 2026					
Gross weight	Normal	kg	316		310		348					
	Sea freight	kg										
Machine dimensions Overall (casing)	W	mm	1206		1206		1206					
	D	mm	1384 (1284)		1384 (1284)		1384 (1284)					
	H	mm	1640		1640		1640					
Net weight		kg	286		280		318					
Max. floor load in operation ³			3394		3335		3708					
Total rated load (EL)		kW	37,9		1,9		1,9					
Heater rating		(kg/h) kW	36 ⁴		36		(86) 40,5					
Motor rating	Drive	W	750		750		750					
	Fan	W	1100		1100		1100					
	Air baffle	W	20		20		20					
Fuse rating ⁵												
3N AC 380-415V 50Hz		A	3 x 63		3 x 10		3 x 10					
3 AC 220-240V 50Hz		A	3 x 100		3 x 16		3 x 16					
Connection EL ⁶												
3N AC 380-415V 50Hz		mm ²	5 x 16		5 x 1,5		5 x 1,5					
3 AC 220-240V 50Hz		mm ²	4 x 25		4 x 1,5		4 x 1,5					
Connections	HP steam		-		-		1/2"					
	Condensate		-		-		1/2"					
	Gas		-		1/2"		-					
Air intake / Venting		mm	DN 150		DN 150		DN 150					
Max. evaporation rate ⁹		l/h	37,0		35,6		38,6					
Evaporation based on RM 70 % to 0 %												
Initial residual moisture ^{7/8}		%	50		50		50					
Load capacity		kg	32	40	32	40	32	40				
Specific energy consumption in kWh/kg of water			0,94	0,97	1,04	0,99	1,04	1,10				
Drying time ^{7/8/10/11/12} Min	Pr 2	Rm 0%	29	35	30	35	31	36				
		4 25%	14	17	14	17	13	17				
Energy consumption ^{7/8/10/11/12}	kWh				Gas	El	Gas	El				
			2	0%	15,1	19,4	16,0	0,7	19,1	0,8	16,6	23,0
			4	25%	7,9	9,5	7,7	0,3	9,5	0,4	8,3	12,0

Type of heating		Electric	Gas	HP-Steam
Drum	Diameter	mm		
	Depth	mm		
	Contents	l		
	Spin speed	rpm		
	Circumference speed	m/s		
	Ø Door opening	mm		
Fan	Circulation capacity (0 mbar) at max. permissible dynamic pressure of 3 mbar	1000 / 1100* 860 / 1010*	1070 / 1080* 950 / 1010*	1060 / 1110* 960 / 1040*
		*Profitronic M	*Profitronic M	*Profitronic M
Material	Plinth	Galvanised sheet steel		
	Drum	Chrome steel 1.4016		
	Air duct	Galvanised sheet steel		
	Casing	Galvanised sheet steel, powder-coated, Octoblu		
	Option: Front panel	Chrome nickel steel 1.4301		
Largest removable component		Dryer drum: Ø 1108 mm / Depth 900 mm		
Disassembly/Assembly time approx. h		2 x 3,0 / 2 x 3,5		

Heat dissipation to ambient room: 1106 W

Acoustic pressure level: L_{PA} 62 dB (A)

Acoustic power level: L_{WA} 73,6 dB (A) according to ISO 9614 Part 2

Test marks:

- 1) Natural gas / Liquid gas
- 2) Values apply for 10 bar steam pressure
- 3) Laundry weight with 50% residual moisture – load ratio 1:20
- 4) Convertible to 31,5 kW, 27,0 kW, 22,5 kW, 18,0 kW, 13,5 kW or 9,0 kW
- 5) Operating category: gL
- 6) Min. cross-section according to VDE 0100 Part 430 / Group 2
- 7) Type of laundry: Programme 1, 2 Turkish towels (50% RM)
3, 4, 5 Cottons – Standard load (A) (50% RM)
- 8) Residual moisture calculated according to DIN 11901 and DIN 11902
- 9) Evaporation based on RM 70% to 0%
- 10) Values may vary according to type of laundry
- 11) Values adjusted to 50% residual moisture and 23°C ambient room temperature
- 12) Values refer to entire programme duration (incl. cool down to 50°C)

Cottons

Programme 2	- Cottons dry	0% Residual moisture
Programme 4	- Cottons moist I	25% Residual moisture