

Octoplus Tumble Dryers

PT 7186 Vario, PTT 7189 Vario

- Powerplus** A performance that offers more with powerful heater elements for fast heat-up and short cycles. Large drum volume for high laundry loads and intelligent solutions for reliable results - Professional, commercial technology.
- Careplus** The patented honeycomb drum ensures laundry is cared for - air pockets provide cushion protection and reduce fibre wear. SoftLift ribs ensure traction is increased, this ensures that the laundry travels further and has extended exposure to the heated air flow.
- Flexplus** Profitronic L Vario controls - Electronic controls with multi-function selector and user navigation screen. Programme delay and time left display to enable the user to manage their time efficiently. Wide range of standard programmes as well as a number of special programmes such as table linen, pillows and outerwear & reproofing.
- Ecoplus** A sustainable, cost effective performance, achieving optimum results by utilising sensitive electronic moisture control and a reversing drum action. Robust design using recyclable materials for maximum sustainability.
- Comfortplus** A simple, user-friendly solution when selecting programmes by using rotary switch and pushbuttons. With a large drum opening for simple loading and unloading.

	 <p style="text-align: center;">PT 7186 Vario</p>	 <p style="text-align: center;">PTT 7189 Vario</p>
Tumble dryer		

Design		
Frontloader, door opening [Ø mm]	440	440
Suitable for stacking	-	x
Drying system		
Vented	x	x
Exhaust diameter [mm]	100	2 x 100
Capacity		
max. load [kg]	8 ¹	2 x 8 ¹
Patented Honeycomb drum volume [litres]	180	2 x 180

¹ 1:25 [kg] * Electro zinc plated x Standard feature o Optional feature - Feature not available

Tumble dryer

	PT 7186 Vario	PTT 7189 Vario
Controls		
PROFITRONIC L Vario	x	x
Slot for communication module	x	x
Connection options		
Communication module with serial interface	o	o
Payment system	o	o
Peak load cut-out	-	-
Heating		
Electric (EL), Gas (G), Steam (D)	EL/G	EL
Electrical connection (electric heating)		
1N AC 220-240 V 50 Hz with cable	5.79 kW/1 x 25 A	2 x (5.79 kW/1 x 25 A)
3N AC 400 V 50 Hz with cable	8.5 kW/3 x 16 A	2 x (8.5 kW/3 x 16 A)
3 AC 440 V 60 Hz	8.5 kW/3 x 16 A	-
Electrical connection (gas heating)		
1N AC 220-240 V 50 Hz	0.48 kW/1 x 10 A	-
Dimensions, weight (electric heating)		
External dimensions H/W/D [mm]	1020/700/763	1920/700/763
Net weight [kg]	78	180
External finish		
Front, sides and lid octobblue, rear panel *	x	x
Front and lid stainless steel, sides octobblue, rear panel *	o	o
Sound levels (IEC 704-1 and 704-2-4)		
	64.9 dB	TBA
Floor load		
Maximum floor load in operation	1000 N	TBA
Frequency	-	-

1 1:25 [kg] * Electro zinc plated x Standard feature o Optional feature - Feature not available

Miele Professional preserves the right to change the machines and specification at anytime, without any prior notice.
All information printed is only for information and never legally binding.



For all enquiries, please contact Miele Professional

Miele Company Limited, Fairacres,
Marcham Road, Abingdon, OX14 1TW
www.Miele-Professional.co.uk

E: miele-professional@miele.co.uk
T: 01235 233 523
F: 01235 405 636

Miele
PROFESSIONAL