## WashPlus Washer-Extractors

PW 6107, PW 6137, PW 6167 & PW 6207

**Powerplus** A performance that offers more with powerful heater elements for fast heat-up and short cycles.

Large drum volume for high laundry loads and intelligent solutions for reliable results - Professional,

commercial technology.

**Ecoplus** 

Careplus The patented honeycomb drum ensures laundry is cared for. The profiled pattern on the drum creates a

protective film of water on which clothing gently slides.

**Flexplus** Profitronic M controls - Freely programmable. Standard programme packages and a total of 199

programme slots. The graphic display combines symbols and text for easy programming and programmes are selected via a rotary dial. The temperatures, holding times, wash times, drum rhythms,

A sustainable, cost effective performance, achieving optimum results using as little water, energy and

spin speeds and dosing are all programmable to suit your needs. Chip card reader fitted as standard.

detergent as necessary. Robust design using recyclable materials for maximum sustainability.

**Comfortplus** A simple, user-friendly solution when selecting programmes by using rotary switch and pushbuttons.

With a large drum opening for simple loading and unloading.

Washer-extractor				
	PW 6107	PW 6137	PW 6167	PW 6207
Design				
Suitable for stacking	-	-	-	-
Door opening Frontloader: [Ø mm]	370	370	370	370
Door opening: Unclean side / clean side [mm]	-	-	-	-
Opening angle	180	180	180	180
Capacity				
Max. load [kg]	10	13	16	20
Honeycomb drum volume [litres]	100	130	160	200
Moisture control				
Spin speed [max. rpm]	1200	1100	1150	1100
g factor	475	400	500	460
Residual moisture %	47	47	46	47
Controls				•
PROFITRONIC M	х	х	х	х
Slot for communication module	х	х	х	х
Dispenser systems				
4 compartment dispenser in machine front	х	х	х	х





Traditor Oxtraditor				
	PW 6107	PW 6137	PW 6167	PW 6207
Connection options				
External liquid dispensing interface	0	0	0	0
Communication module with serial interface	o	o	o	0
Payment system	0	0	0	0
Peak load cut-out	0	0	0	0
Plumbing				
2 x Cold water 1/2" with 3/4" threaded union	х	х	Х	х
1 x Hot water, 1/2" with 3/4" threaded union	х	х	Х	х
Cold water valve for liquid dispensing, 3/4" threaded union	0	o	o	o
Min. flow pressure 100 kPa (1 bar)	х	х	х	х
Max. flow pressure 1000 kPa (10 bar)	х	х	х	х
Drain pump DN 22	-	-	-	-
Dump valve DN 70	х	х	х	х
Heating				
Electric (EL), Gas (G), Steam (D)	EL/G/D	EL/G/D	EL/G/D	EL/G/D
Electrical connection * (electric heating)				•
3N AC 380-415 V 50-60 Hz	11 kW / 3 x 16 A	17 kW / 3 x 25 A	17 kW / 3 x 25 A	22.3 kW / 3 x 35 A
3 AC 440V 60 Hz	11 kW / 3 x 16 A	17 kW / 3 x 25 A	17 kW / 3 x 25 A	22.3 kW / 3 x 35 A
Electrical connection * (gas heating)				•
3N AC 380-415V 50-60 Hz	2.3. kW / 3 x 16 A	2.3 kW / 3 x 16 A	3 kW / 3 x 16 A	4.7 kW / 3 x 16 A
Electrical connection * (steam heating)		'		
3N AC 380-415V 50-60 Hz	2.3. kW / 3 x 16 A	2.3 kW / 3 x 16 A	3 kW / 3 x 16 A	4.3 kW / 3 x 16 A
Dimensions weight (clostric heating)				l
Dimensions, weight (electric heating)  External dimensions H/W/D [mm]	1250/804/925	1250/804/1005	1400/924/1007	1400/924/1140
Net weight [kg]	324	342	454	495
	021	0.2	101	100
External finish				
Front stainless steel, lid and sides octoblue, rear panel *	x	х	х	х
Lid, sides and rear panel in stainless steel	0	0	0	0
Sound levels (IEC 704-1 and 704-2-4)				
Wash	64 (dB re 1pW)	65 (dB re 1pW)		
Spin	76.6 (dB re 1pW)	75.7 (dB re 1pW)		78.5 (dB re 1pW)
Floor load				
Maximum floor load in operation	3970 N	4304 N	5469 N	6076 N
Frequency	20 Hz	18.3 Hz	19.2 Hz	18.3 Hz

<sup>\*</sup>Electro-zinc plated  $\,$   $\,$   $\,$   $\,$   $\,$   $\,$  Standard feature  $\,$   $\,$   $\,$   $\,$  Optional feature  $\,$  - Feature not available

Miele Professional preserves the right to change the machines and specification at anytime, without any prior notice. All information printed is only for information and never legally binding.



## For all enquiries, please contact Miele Professional

Miele Company Limited, Fairacres, E: miele-professional@miele.co.uk
Marcham Road, Abingdon, OX14 1TW T: 01235 233 523

www.Miele-Professional.co.uk F: 01235 405 636

